


Metal Quick - Disconnect Couplings

These quick-disconnect fittings consist of two fitting halves-order coupling bodies (Female halves) and inserts (Male halves) with the same flow size. Fittings withstand pressures from vacuum to 250 psi, Temperatures from -40 to 82°C. In addition to vacuum and pressure applications, These fittings can be used for liquids. Made of chrome-plated brass with stainless steel springs and latch. Valved fittings have acetal shutoff valves that seal the flow path when fitting halves are disconnected.



Quick - Disconnect Bodies - Coupler (Female Fitting Halves)

A Hose Barbs Bodies

Number	Tube ID	Flow Size	Length	Price ฿
Valved Fittings				
3A14 0430	1/8"	1/8"	1.65"	---
3A14 0431	3/16"	1/8"	1.65"	---
3A14 0432	1/4"	1/8"	1.85"	---
3A14 0320	1/4"	1/4"	2.00"	---
3A14 0321	5/16"	1/4"	2.00"	---
3A14 0322	3/8"	1/4"	2.00"	---

Straight - Through Fittings

3A14 0410	1/8"	1/8"	1.65"	---
3A14 0411	3/16"	1/8"	1.65"	---
3A14 0312	1/4"	1/8"	1.85"	---
3A14 0425	1/4"	1/4"	2.00"	---
3A14 0326	5/16"	1/4"	2.00"	---
3A14 0327	3/8"	1/4"	2.00"	---

B NPT(M) Threaded Adapter Bodies

Number	NPT (M)	Flow Size	Length	Price ฿
Valved Fittings				
3A14 0420	1/8"	1/8"	1.10"	---
3A14 0421	1/4"	1/8"	1.10"	---
3A14 0300	1/4"	1/4"	1.15"	---
3A14 0301	3/8"	1/4"	1.15"	---

Straight - Through Fittings

3A14 0400	1/8"	1/8"	1.10"	---
3A14 0401	1/4"	1/8"	1.10"	---
3A14 0305	1/4"	1/4"	1.15"	---
3A14 0306	3/8"	1/4"	1.15"	---

C Compression Fitting Bodies

Number	Tube OD	Flow Size	Length	Price ฿
Valved Fittings				
3A14 0429	1/4"	1/8"	1.77"	---
3A14 0310	1/4"	1/4"	1.87"	---
3A14 0311	3/8"	1/4"	2.00"	---

Straight - Through Fittings

3A14 0409	1/4"	1/8"	1.77"	---
3A14 0315	1/4"	1/4"	1.87"	---
3A14 0316	3/8"	1/4"	2.00"	---

Quick - Disconnect Inserts - Coupler (Male Fitting Halves)

D Hose Barbs Bodies

Number	Tube ID	Flow Size	Length	Price ฿
Valved Fittings				
3A14 0471	1/8"	1/8"	1.55"	---
3A14 0472	3/16"	1/8"	1.75"	---
3A14 0473	1/4"	1/8"	1.58"	---
3A14 0340	1/4"	1/4"	1.85"	---
3A14 0341	5/16"	1/4"	1.85"	---
3A14 0342	3/8"	1/4"	1.68"	---

Straight - Through Fittings

3A14 0451	1/8"	1/8"	1.55"	---
3A14 0452	3/16"	1/8"	1.75"	---
3A14 0453	1/4"	1/8"	1.58"	---
3A14 0345	1/4"	1/4"	1.85"	---
3A14 0346	5/16"	1/4"	1.85"	---
3A14 0347	3/8"	1/4"	1.68"	---

E NPT(F) Threaded Adapter Inserts

Number	NPT (F)	Flow Size	Length	Price ฿
Valved Fittings				
3A14 0462	1/8"	1/8"	1.57"	---
3A14 0363	1/4"	1/8"	1.72"	---
3A14 0352	1/4"	1/4"	1.75"	---

Straight - Through Fittings

3A14 0442	1/8"	1/8"	0.95"	---
3A14 0343	1/4"	1/8"	1.15"	---
3A14 0357	1/4"	1/4"	1.25"	---

F Hose Barb Elbow Inserts

Number	Tube ID	Flow Size	Length	Price ฿
Valved Fittings				
3A14 0477	1/8"	1/8"	1.18"	---
3A14 0478	1/4"	1/8"	1.18"	---
3A14 0392	1/4"	1/4"	1.28"	---
3A14 0393	3/8"	1/4"	1.28"	---

Straight - Through Fittings

3A14 0457	1/8"	1/8"	1.18"	---
3A14 0458	1/4"	1/8"	1.18"	---
3A14 0397	1/4"	1/4"	1.28"	---
3A14 0398	3/8"	1/4"	1.28"	---

G NPT(M) Threaded Adapter Inserts

Number	NPT (M)	Flow Size	Length	Price ฿
Valved Fittings				
3A14 0460	1/8"	1/8"	1.33"	---
3A14 0461	1/4"	1/8"	1.30"	---
3A14 0350	1/4"	1/4"	1.53"	---
3A14 0351	3/8"	1/4"	1.40"	---

Straight - Through Fittings

3A14 0440	1/8"	1/8"	1.03"	---
3A14 0441	1/4"	1/8"	1.13"	---
3A14 0355	1/4"	1/4"	1.25"	---
3A14 0356	3/8"	1/4"	1.25"	---

H Compression Elbow Inserts

Number	Tubing OD	Flow Size	Length	Price ฿
Valved Fittings				
3A14 0475	5/32"	1/8"	1.18"	---
3A14 0476	1/4"	1/8"	1.18"	---
3A14 0390	1/4"	1/4"	1.28"	---
3A14 0391	3/8"	1/4"	1.28"	---

Straight - Through Fittings

3A14 0455	5/32"	1/8"	1.18"	---
3A14 0456	1/4"	1/8"	1.18"	---
3A14 0395	1/4"	1/4"	1.28"	---
3A14 0396	3/8"	1/4"	1.28"	---

I Compression Inserts

Number	Tubing OD	Flow Size	Length	Price ฿
Valved Fittings				
3A14 0468	5/32"	1/8"	1.53"	---
3A14 0469	1/4"	1/8"	1.45"	---
3A14 0330	1/4"	1/4"	1.72"	---
3A14 0331	3/8"	1/4"	1.68"	---

Straight - Through Fittings

3A14 0448	5/32"	1/8"	1.13"	---
3A14 0449	1/4"	1/8"	1.15"	---
3A14 0335	1/4"	1/4"	1.25"	---
3A14 0336	3/8"	1/4"	1.38"	---